

**MODEL NO. 200 "GAUGE MINDER" PRESSURE LIMITING VALVE
(Shut Off Adjustable From 50 to 5000 P.S.I.G.)**

① ② ③ STANDARD MODELS SPECIFICATIONS

200-AO-00
5000 P.S.I.G. Working Pressure, Aluminum Body & 316 S.S. Wetted Internals; 1/4" FNPT Connections; Buna N & Teflon® Seals. Weight – 1 lb./.45 Kilograms

200-BO-00
5000 P.S.I.G. Working Pressure, Brass Body with 316 S.S. Wetted Internals; 1/4" FNPT Connections; Buna N & Teflon® Seals. Weight – 3.0 lbs./1.36 Kilograms

200-SO-00
5000 P.S.I.G. Working Pressure, 316 S.S. Body & Wetted Internals; 1/4" FNPT Connections; Buna N & Teflon® Seals. Weight – 3 lbs./1.36 Kilograms

200-BH-00
10,000 P.S.I.G. Working Pressure, Brass Body with 316 S.S. Wetted Internals; 1/2" FNPT Connections; Buna N & Teflon® Seals. Weight – 2.5 lbs./1.14 Kilograms

200-SH-00
10,000 P.S.I.G. Working Pressure, 316 S.S. Body & Wetted Internals 1/2" FNPT Connections; Buna N & Teflon® Seals. Weight – 2.5 lbs./1.14 Kilograms

OPTIONS

④ SEALS

- 0. Buna N O-Rings (**Standard**)
- 1. Viton® O-Rings
- 2. Neoprene O-Rings
- 5. Ethylene Propylene O-Rings
- 9. Special (Uncoded Options)

⑤ OPTIONS

- 0. None
- 7. Factory Presetting of Shut-Off Point (**Above 1500 PSIG**)
- 8. Factory Presetting of Shut-off Point (**Up to 1500 PSIG**)
- 9. Special (Uncoded Options)

NOTE: MINIMUM SET PRESSURE IS 50 PSIG FOR MODEL 200 "GAUGE MINDERS"

PART NUMBERING SYSTEM

